

COMPLEX

ANTIFREEZE/COOLANT GLOBAL EXTENDED LIFE ANTIFREEZE/ COOLANT PRE-MIX

<u>TEST</u>	<u>SPECIFICATION</u>	<u>TYPICAL</u>
BOILING POINT (ERBP)	MIN. 226 F	226 F
SPECIFIC GRAVITY @ 60/60 F	1.063 - 1.073	1.065
pH (AS-IS)	7.0 - 11.0	8.5
RESERVE ALKALINITY	REPORT	2
COLOR	YELLOW	YELLOW
FREEZING POINT (AS-IS)	-34 F	-34 F

THIS PRODUCT MEETS THE FOLLOWING INDUSTRY SPECIFICATIONS:

ASTM D 3306	CUMMINS 3666132	JOHN DEERE H-5
ASTM D 4985	DETROIT DIESEL 7SE298	JOHN DEERE 8650-5
ASTM D 5345	GM 1825M	MACK TRUCK 014GS17004
ASTM D 4656	GM 1899M	FREIGHTLINER 48 22880
ASTM D 6210	ATA RP 329	
ASTM D 6471	SUBARU	
ASTM D 6472	NISSAN	
FORD ESE-M97B44-A	AUDI	
FORD ESE-M97B44-A	BMW	
CATERPILLAR EC-1 SECTIONS 3.1.1 & 3.1.2		
CHRYSLER MS-9769	MERCEDES	
CUMMINS 90T8-4	NAVISTAR B1 (B6-008GO)	